



10/501315



*[Handwritten signature]*

INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales

Rec'd PCT/PTO 13 JUL 2004 **PRIORITY DOCUMENT**  
SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)

NP10 800  
REC'D 25 MAR 2003  
WIPO PCT


I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the attached copy of the request for grant of a Patent (Form 1/77) bears an amendment, effected by this office, following a request by the applicant and agreed to by the Comptroller-General.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed *[Handwritten signature: J. Behan]*

Dated 27 February 2003

**BEST AVAILABLE COPY**



**Request for grant of a patent**  
*(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)*

23 JAN 2002

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP9 1RH

1. Your reference JLWM/P33387GB

2. Patent application number  
*(The Patent Office will fill in this part)*

**0201479.3**

3. Full name, address and postcode of the or of each applicant *(underline all surnames)*

Aurora Limited  
Unit 1B, The Courtyard  
Alban Park  
Hatfield Road  
St. Albans  
Hertfordshire AL4 0LA  
England and Wales

Patents ADP number *(if you know it)*

If the applicant is a corporate body, give the country/state of its incorporation

8309809001

4. Title of the invention

LIGHT FITTING

5. Name of your agent *(if you have one)*

"Address for service" in the United Kingdom to which all correspondence should be sent *(including the postcode)*

Kilburn & Strod  
20 Red Lion Street  
London  
WC1R 4PJ

GOMMERVILLE & RUSHTON  
25 RUSVENOR ROAD  
ST ALBANS  
HERTS AL1 3AW

Patents ADP number *(if you know it)*

125001

1511001

5/11/03

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and *(if you know it)* the or each application number

Country

Priority application number  
*(if you know it)*

Date of filing  
*(day / month / year)*

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
*(day / month / year)*

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? *(Answer 'Yes' if:*

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

YES

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 8 ✓

Claim(s) 4 ✓

Abstract 1 ✓

Drawing(s) 8 + 8 RW

10. If you are also filing any of the following, state how many against each item.

~~Priority documents~~

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date 22/01/02

*John P. Stodg*  
KILBURN & STODG

12. Name and daytime telephone number of person to contact in the United Kingdom

Mr. J L W Miller

Tel: 020 7539 4200

**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

## LIGHT FITTING

The present invention relates to light fittings, such as downlighters. The invention also extends to light fittings including lamps comprising dichroic lamp bulbs, such as 12v bulbs.

Known downlighters have a circular section and, in order to remove the lamp, for replacement purposes, a circlip is provided for holding the lamp in position. To remove the lamp, the circlip is first removed and the lamp may then be changed. Alternatively, a lamp may be held to a circular body of the fitting by a circular retainer which may be locked in position on a surrounding body of the downlighter with a twisting action. To remove the bulb, the circular retainer is twisted inside the circular body and may then be removed. These structures designed for enabling lamp replacement may not be suitable for all applications.

According to a first aspect of the present invention there is provided a light fitting having a support surround and a front facia, and a facia retainer for holding the front facia in position, the facia retainer being resilient for enabling removal of the facia from an installed position by a generally translational movement. This movement may be provided by application of force in an axial direction of the light fitting.

This is advantageous, since the front facia may be arranged to retain a lamp and the facia and/or lamp may easily be removed for replacement or servicing purposes with a simple force applied to the light fitting, without the requirement to remove a circlip, or the requirement to twist before removal. Since a twisting action is not required, the twisting action itself resulting in the requirement for circular facia and surround components in the prior art, it is possible to form the light fitting, support surround, front facia and/or any lamp with a non-circular section, such as when viewed in the direction of main light projection from a lamp of the light fitting.

Preferably, a lamp retainer and a lamp are provided, the lamp being resiliently retained by the lamp retainer such that the lamp may be moved relative to the retainer. This is advantageous in that it allows the lamp to be pushed, such as by a finger of a person changing the lamp, away from the retainer such that the finger may then be used to pull the retainer, such as for removing the lamp retainer and lamp from the light fitting.

According to a second aspect of the present invention there is provided a light fitting having a support surround, a lamp retainer, and a lamp, the lamp being resiliently retained by the lamp retainer such that the lamp may be moved relative to the retainer.

Preferably, a front fascia and a fascia retainer for holding the front fascia in position are provided, the fascia retainer being resilient for enabling removal of the fascia from an installed position by a generally translational movement.

A number of optional features which may be applicable to either of the aforementioned aspects of the invention will now be discussed.

The lamp retainer may form the front fascia. In this case, the lamp may be resiliently retained by the front fascia such that the lamp may be moved relative to the front fascia. Thus, the lamp may be moved relative to the lamp retainer in a rearward direction, for example, by tool or a finger of a person replacing or servicing the light fitting, and the tool or finger may then be used to pull the front fascia and lamp away from the support surround for replacement or servicing of the lamp.

Alternatively, the lamp retainer may comprise a light tube extending axially in front of the lamp. The light tube may extend from the lamp to the front fascia. Thus, the light tube may space the lamp rearwards relative to a front surface of the front fascia for providing a desired projection of light from the light fitting. The light tube may thus form a light baffle.

The front fascia may have a non-circular cross-section. The cross-section may be a regular polygon. The cross-section may be hexagonal or square.

The support surround may include at least one spring arm for holding the light fitting in place on a layer of building material.

5 The front facia may be directly retained by the facia retainer to the support surround. Alternatively, the front facia may be attached by the facia retainer to an intermediate member, the intermediate member being connected to the support surround. In this case, the intermediate member may be pivotally coupled to the support surround. The intermediate member may have a non-circular cross-section. This cross-section may be a regular polygon, such as a hexagon or square.

10 The facia retainer may comprise at least one spring clip. Preferably, a pair of said spring clips are provided, located on opposed sides of the light fitting. The spring clips are preferably secured to the front facia.

15 Preferably, a spring is provided for biasing the lamp towards the front facia. The spring is preferably arranged to provide force in response to axial extension thereof. The spring may be a helical spring such as of spring steel. Preferably, at least two said springs are provided, each extending from one end of the lamp opposite a lens end thereof to the lamp retainer. Where an intermediate member is provided, said springs may extend from an end of the lamp opposite the lens end thereof to the intermediate member. The  
20 intermediate member may be connected to the facia by one or more springs. Preferably, each spring which extends from an end of the lamp opposite the lens end thereof, extends from an electrical connector. The electrical connector may be mounted on one or more electrical connector pegs located on the lamp. Preferably, two opposed springs extend from the electrical connector to the  
25 lamp retainer in the form of the front facia or intermediate member, where provided, so as to retain the lamp in position.

30 Preferably, the facia includes a recessed ledge for engaging the perimeter of a lamp. Where a lamp is provided, this may have a front face which comprises a flat panel. The recessed ledge may enable a person wishing to change a lamp of the light fitting to push the lamp backwards away from the

recessed ledge, such as with a finger, and then to pull on the recessed ledge to remove the front facia and lamp from the support surround.

Preferably, a lamp is provided, the lamp having a flat front surface.

The light fitting may comprise a downlighter.

5 According to a further aspect of the invention there is provided a building having a layer of building material and a light fitting as in either of the aforementioned aspects of the invention secured to a layer of building material.

---

10 The support surround may be located around an aperture formed through the layer of building material. The support surround preferably has a flat front surface. The front facia may have a front surface flush with the front surface of the support surround. The lamp may be recessed behind the front facia.

The present invention may be carried out in various ways and a number of preferred light fittings in accordance with the invention will now be described by way of example with reference to the accompanying drawings in  
15 which:

Fig.1 is an exploded perspective view of parts of a preferred light fitting in accordance with the invention;

Figs.2A to 2H are various elevations of the light fitting of Fig.1;

Figs.3A to 3G are various elevations of a lamp of the light fitting;

20 Figs.4A to 4C are three views demonstrating removal of a front facia and lamp from the light fitting;

Fig.5A is a cross-section of part of a modified light fitting and Fig.5B is a view in the direction of arrow A in Fig.5A;

25 Fig.6A is a cross-section of part of the light fitting components of Fig.1 and Fig.6B is a view in the direction of arrow B in Fig.6A;

Fig.7A is a cross-section of part of the second modified light fitting in accordance with the invention and Fig.7B is a view in the direction C in Fig.7A;

30 Fig.8A to 8G are various views of an optional light tube for use with any of the light fittings of Figs.1 to 7B;

Figs.9A to 11B show alternative light fittings, having a square form, Figs.9B, 10B and 11B being views in the directions D, E and F respectively, in Figs.9A, 10A and 11A; and

5 Figs.12A to 12G are various views of a lamp with a square form for use with the fittings of Figs.9A to 11B.

Fig.1 shows a preferred embodiment of a light fitting 10 in the form of a downlighter in accordance with a preferred embodiment of the present invention. The downlighter 10 includes a hexagonal support surround 12 having a hexagonal ring-like front flange 14 and an inner hexagonal wall 16, each of six arms 18 of the wall extending rearwardly from and perpendicular to the flat front flange 14. The wall 16 includes two connection flanges 20, each holding a support spring 22 for holding the light fitting 10 in place with a rear surface 24 of the flange 14 abutting against and parallel to a layer of building material 26 in the form of part of a ceiling in a building 28 having a wall 30 (Fig.4A). One of the connector flanges 20 also holds a bracket 32, a finger 34 of the bracket passing through and being retained by a coil portion 36 of the adjacent support spring 22. The bracket 32 is L-shaped and includes a rearwardly extending portion 38 and an end portion 40 attached and perpendicular thereto. Attached to the end portion is an electrical connector 42, comprising a housing 44 with a lid 46 and a wiring connection device 48. The wiring connection device 48 enables lamp wires 50 to be connected to mains wires 52, optionally via transformer wires 54 and transformer 56.

As shown in Fig.4A, the lamp wires 50 each terminate at one end 58 thereof at an electrical connector 60 including terminals 62 for electrical connection to lamp pegs 64 of a lamp 66. As shown in Figs.3A to 3G, the lamp 66 has a hexagonal cross-section when viewed along a longitudinal axis thereof. In the case of a light fitting with a transformer 56, the lamp may be a 12v dichroic lamp 66. The hexagonal lamp 66 includes six reflector faces 68 which are each slightly outwardly concave, each including a series of parallel outwardly convex reflector portions 70. The lamp 66 has a flat front face 72

(see Fig.4A) having a perimeter 74. The lamp 66 has a central bulb 75. The lamp 66 is retained in place in the light fitting 10 by a hexagonal lamp retainer 76 in the form of a front facia of the light fitting. The front facia 76 includes a hexagonal front flange 78 and a rearwardly extending hexagonal wall 80 having six arm portions 82. Two of the arm portions have retainer devices 84 secured thereto, the retainer devices 84 each have a V-shaped portion 108. The retainer devices 84 are thus adapted to retain the front facia 76 on a hexagonal intermediate member 86 which may be hinged by hinge portions 88 using pivot pins 90, which may take the form of rivets 90, to the support surround 12. The intermediate member 86 includes an interior peripheral ledge 92 which the clips 84 are adapted to engage with a spring force, so as to maintain the front facia in a fixed position relative to the intermediate member 86. As shown by Figs.2E and 2F, as well as 2G and 2H, the intermediate member 86 may be tilted one way or the other, by virtue of the hinge portions 88, so that light emitted from the lamp 66 may be directed as desired.

Two helical springs 94 (only one of which is shown in Fig.4A for the purposes of clarity) extend from the electrical connector 60 to spring connector holes 96 (Fig.1) on opposite arms 82 of the wall 80 of the front facia 76, or alternatively to modified connection portions 98 (Fig.4C) comprising rearwardly extending flanges 100 of the front facia 76 together with apertures 102.

As shown in Fig.4A, the springs 94 are under tension when the lamp 66 is fitted, such that the lamp 66 is compressed between the connector 60 and a recessed peripheral ledge 104 of the front facia 76.

As shown in Figs.4A, 4B and 4C, to remove the lamp 66 for servicing or replacement, from the installed position shown in Fig.4A, using a finger 106 or a suitable tool (not shown), a person may first push the lamp 66 in the rearward or upper direction shown by the arrow R in Fig.4A, such that the lamp moves in this direction relative to the lamp retainer/front facia 76. The finger 106 or tool may then be engaged behind the ledge 104 in order to pull the front facia

forwards or downwards in the direction of arrow F in Fig.4B. It will be appreciated that the springs 94 advantageously enable the lamp 66 to be moved relative to the lamp retainer 76 so that purchase may easily be gained upon the retainer 76 for removal thereof together with the lamp. Additionally, the  
5 springs 84 enable the retainer/front fascia 76 to be released with a simple forward movement and this enables the various components of the light fitting 10 to have a non-circular section, in this case a regular hexagon. Thus, extending flexible V-shaped portion 108 of each spring clip 84 is adapted for resilient compression inwardly towards the adjacent wall arm 82 of the front  
10 fascia, as the front fascia 76 moves from the position 4A to the position of 4B. Fig.4C simply shows the support surround 12, intermediate member 86, and retainer/front fascia 76 and clips 84 in a configuration once the front fascia has been removed from retention by the intermediate member by virtue of the clips 84.

15 Figs.7A and 7B show a modified light fitting 10' having similar components to those shown in the embodiment of Fig.1, including a support surround 12', front fascia 76', clips 84', with a modified intermediate member 86' which is bucket-shaped and hinged at a hinge portion 88' to the support surround 12' at one side of the light fitting. This enables greater rotation to one  
20 side than the embodiment of Fig.1 and thus may be suitable for application to a ceiling for lighting of a wall such as in the region of a picture. Fig.5A and Fig.5B show a further modification, in which the intermediate member 86 is omitted, such that the front fascia 76'' is directly retained by the support surround 12'', the recessed ledge 104'' of the front fascia 76'' retaining the  
25 lamp 66 and the spring clips 84'' releasably retaining the front fascia 76'' in position on the support surround 12'', with the clips 84'' resiliently engaging behind peripheral ledge 92'' of the support surround 12''.

Figs.8A to 8G show an optional light tube or baffle 108 which may take the place of the front fascia 76 as the lamp retainer and may be positioned  
30 between the lamp 66 and the front fascia 76. Thus, when the light tube 108 is

used, the springs 94 may be connected to connection apertures 110 on the light tube 108 for clamping the lamp 66 between the connector 60 and the light tube 108, and the light tube 108, which consists of a hollow hexagonal and longitudinally extending tube 112 may be connected by connection springs 114 to the apertures 96,96' for clamping the light tube to the front facia 76, thus holding the lamp 66 in position.

Instead of having a hexagonal form, the light fitting 10 may have other forms when viewed in the front or rearward direction thereof, such as other polygonal or regular polygonal shapes, such as a square shape. Figs.9A to 11B show three square embodiments equivalent to the three hexagonal embodiments shown in Figs.5A to 7B. Thus, in Figs.10A and 10B the square support surround 12''' pivotally supports a square intermediate member 86''' which holds a square front facia 76'''. In the embodiment of Figs.11A and 11B, a square front facia 76'''' pivotally supports a bucket-shaped intermediate member 86'''' at a side hinge 88''', the intermediate member 86'''' supporting the front facia 76'''' by springs 84'''''. Furthermore in Figs.9A and 9B, the front facia 76'''''' is retained directly by support 12'''''' using springs 84'''''''. A square lamp 66' for use with the embodiments of Figs.9A to 11B is shown in Figs.12A to 12G and includes four main reflector faces 68' each including a series of parallel convex reflector portions 70', a bulb 116 and electrical pegs 64'.

It will be appreciated that various modifications may be made to the embodiments described herewith without departing from the scope of the invention as defined by the accompanying claims as interpreted under patent law.

## CLAIMS

1. A light fitting having a support surround and a front facia, and a facia retainer for holding the facia in position, the facia retainer being resilient for enabling removal of the facia from an installed position thereof by a generally translational movement.
2. A light fitting as claimed in claim 1 in which a lamp retainer and a lamp are provided, the lamp being resiliently retained by the lamp retainer such that the lamp may be moved relative to the retainer.
3. A light fitting having a support surround, a lamp retainer, and a lamp, the lamp being resiliently retained by the lamp retainer such that the lamp may be moved relative to the retainer.
4. A light fitting as claimed in claim 4 in which a front facia and a facia retainer for holding the facia in position are provided, the facia retainer being resilient for enabling removal of the facia from an installed position thereof by generally translational movement.
5. A light fitting as claimed in any one of claims 2 to 4 in which the lamp retainer forms the front facia.
6. A light fitting as claimed in any one of claim 2 or claim 4 in which the lamp retainer comprises a tube extending axially in front of the lamp.
7. A light fitting as claimed in claim 1 or claim 4 or any preceding claim when dependent upon claim 1 or claim 4 in which the front facia has a non-circular section.

8. A light fitting as claimed in claim 7 in which the cross-section is a regular polygon.

5 9. A light fitting as claimed in claim 7 or claim 8 in which the cross-section is hexagonal.

10. A light fitting as claimed in claim 7 or claim 8 in which the cross-section is square.

---

10 11. A light fitting as claimed in any preceding claim in which the support surround includes at least one spring arm for holding the light fitting in place on a layer of building material.

15 12. A light fitting as claimed in any claim 1 or claim 4 or any claim dependent on claim 1 or claim 4 in which the front facia is directly retained by the facia retainer to the support surround.

20 13. A light fitting as claimed in claim 1 or claim 4 or any one of claims 5 to 11 when dependent upon claim 1 or claim 4 in which the front facia is attached by the facia retainer to an intermediate member, the intermediate member being connected to the support surround.

25 14. A light fitting as claimed in claim 13 in which the intermediate member is pivotally coupled to the support surround.

15. A light fitting as claimed in claim 13 or claim 14 in which the intermediate member has a non-circular section.

30 16. A light fitting as claimed in claim 15 in which the cross-section is a regular polygon.

17. A light fitting as claimed in claim 16 in which the cross-section is hexagonal.

5 18. A light fitting as claimed in claim 15 or claim 16 in the cross-section is square.

10 19. A light fitting as claimed in claim 1 or claim 4 or any preceding claim when dependent upon claim 1 or claim 4 in which the facia retainer comprises at least one spring clip.

20. A light fitting as claimed in claim 19 in which a pair of said spring clips provided, located on opposed sides of the light fitting.

15 21. A light fitting as claimed in claim 19 or claim 20 in which each spring clip is secured to the front facia.

20 22. A light fitting as claimed in claim 2 or claim 3 or any preceding claim when dependent upon claim 2 or claim 3 in which a spring is provided for biasing the lamp towards the front facia.

23. A light fitting as claimed in claim 22 in which the spring is a helical spring.

25 24. A light fitting as claimed in claim 22 or claim 23 in which two said springs are provided, each extending from an end of the lamp opposite a lens end thereof to the lamp retainer.

30 25. A light fitting as claimed in claim 24 in which each spring extends from an electrical connector to the lamp retainer.

26. A light fitting as claimed in claim 1 or claim 4 or any preceding claim when dependent on claim 1 or claim 4 in which the fascia includes a recessed ledge for engaging the perimeter of a lamp.

5

27. A light fitting as claimed in any preceding claim which includes a lamp, the lamp having a flat front surface.

---

10

28. A light fitting as claimed in any preceding claim which comprises a downlighter.

29. A light fitting substantially as described herein with reference to the accompanying drawings.

15

30. A building have a layer of building material and a light fitting as claimed in any preceding claim secured to the building layer.

31. A building as claimed in claim 30 in which the layer of building material forms part of the ceiling.

20

32. A building as claimed in claim 30 or claim 31 in which the support surround has a flat front flange lying adjacent a substantially flat area of the building layer.

25

33. A building as claimed in claim 30 or claim 31 or claim 32 in which a lamp is provided connected to the light fitting, the lamp being substantially recessed behind the layer of building material.

**ABSTRACT****LIGHT FITTING**


5           A light fitting 10 has a support surround 12, front facia 76 and optional intermediate member 86 for pivotally supporting the front facia 76. The front facia 76 is removable retained by the intermediate member 86 or support surround 12 by spring clips 84. A lamp 66 is held in position by springs 94, either to the front facia 76 or to a light tube 108.

10


(Figure 4A)




2/8



3/8



4/8



01/00













Fig 5B


6/8



7/8



8/8



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- BLACK BORDERS
- IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT OR DRAWING
- BLURRED OR ILLEGIBLE TEXT OR DRAWING
- SKEWED/SLANTED IMAGES
- COLOR OR BLACK AND WHITE PHOTOGRAPHS
- GRAY SCALE DOCUMENTS
- LINES OR MARKS ON ORIGINAL DOCUMENT
- REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**